

Part number:

**HYDROMA**

HYDRAULICKÉ SYSTÉMY

**HIDROMA
SYSTEMS**

UKŁADY HYDRAULICZNE

HYDROMA

ГИДРАВЛИЧЕСКИЕ СИСТЕМЫ

PRESSURE FILTERS

CLOGGING INDICATORS

INDICATOR SERIE DESCRIPTION FOR PRESSURE FILTERS SERIES

NBR	FKM	Differential ELECTRICAL indicators with THERMOSTAT 30° C	
T0	DB	Setting 130 kPa (1,3 bar)	FPH - FPO
T2	DE	Setting 500 kPa (5 bar)	FPA - FPB - FPD - FPL - FPM
T3	DF	Setting 800 kPa (8 bar)	FPA - FPB - FPC - FPD - FPL - FPM
T6	DD	Setting 250 kPa (2,5 bar)	FPA - FPB - FPC - FPD - FPG - FPL - FPM - FPO
SPDT differential switch. C.C. 14 - 30 V: > max resistive or inductive load 4 - 3 A respectively C.A. 125-250 V: > max resistive or inductive load 1 A - Protection IP65 - Connector DIN 43650			
NBR	FKM	Differential VISUAL ELECTRICAL indicators	
70	E0	Setting 130 kPa (1,3 bar)	FPH
76	E6	Setting 250 kPa (2,5 bar)	FPA - FPB - FPD - FPL - FPM
72	E2	Setting 500 kPa (5 bar)	FPA - FPB - FPC - FPD - FPL - FPM
73	E3	Setting 800 kPa (8 bar)	FPA - FPB - FPC - FPD - FPL - FPM
SPDT differential switch. C.C. 14 - 30 V: > max resistive or inductive load 4 - 3 A respectively C.A. 125-250 V: > max resistive or inductive load 1 A - Protection IP65 - Connector DIN 43650			
NBR	FKM	Differential ELECTRICAL indicators VANDAL PROOF	
M2	-	Setting 500 kPa (5 bar)	FPA - FPB - FPC - FPD - FPL - FPM
M3	-	Setting 800 kPa (8 bar)	FPA - FPB - FPC - FPD - FPL - FPM
M6	-	Setting 250 kPa (2,5 bar)	FPA - FPB - FPD - FPL - FPM
SPDT differential switch. C.C. 14 - 30 V: > max resistive or inductive load 4 - 3 A respectively C.A. 125-250 V: > max resistive or inductive load 1 A - Protection IP65 - Connector DIN 43650			

