

Part number:

HYDROMA

HYDRAULICKÉ SYSTÉMY

**HIDROMA
SISTEMS**

UKŁADY HYDRAULICZNE

HYDROMA

ГИДРАВЛИЧЕСКИЕ СИСТЕМЫ



CLIENTE / COMPANY

RICHIEDENTE / REFERENCE

ACQUA-OLIO / WATER-OIL

PORTATA OLIO OIL FLOW RATE		lpm
POTENZA INSTALLATA TOTAL POWER		KW
POTENZA DA DISSIPARE POWER TO BE DISSIPATED		KW
TEMPERATURA INGRESSO OLIO OIL TEMPERATURE INLET		°C
TEMPERATURA INGRESSO ACQUA WATER TEMPERATURE INLET		°C
VISCOSITA' OLIO @ 40°C OIL VISCOSITY @ 40°C		cst
PRESSIONE DI LAVORO WORKING PRESSURE		bar
PORTATA ACQUA WATER FLOW		lpm

ARIA-OLIO / AIR-OIL

PORTATA OLIO OIL FLOW RATE
POTENZA INSTALLATA TOTAL POWER
POTENZA DA DISSIPARE POWER TO BE DISSIPATED
TEMPERATURA INGRESSO OLIO OIL TEMPERATURE INLET
TEMPERATURA ARIA MAX MAX AIR TEMPERATURE
VISCOSITA' OLIO OIL VISCOSITY
PRESSIONE DI LAVORO WORKING PRESSURE

MATERIALE MATERIAL ☐**RAME / COPPER** ☐**PER ACQUA DI MARE / FOR SEA WATER** ☐**AISI 304 / AISI 304** ☐**AISI 316 / AISI 316** ☐

Power to be dissipated:

- Industrial : 30% of the total power
- Mobile : 40% of the total power.

PIASTRE / PLATES ☐
BRASATE / BRAZED ☐
ISPEZIONABILI / DISMANTLING
☐ **TIPO DI VENTILAZIONE TYPE OF FAN UNIT**☐ **12V CC / 12 V DC**☐ **24V CC / 24 V DC**☐ **MONOFASE 230V / SINGLEPHASE 230V AC**☐ **TRIFASE 230/400V / THREEPHASE 230/400V AC**☐ **50 Hz**☐ **60 Hz**☐ **IDRAULICO / HYDRAULIC**☐ **GR1**☐ **GR2**☐ **GR3****ALTRO / OTHER**☐ **GRUPPO DI RAFFREDDAMENTO AUTONOMO**
COOLING SYSTEM UNIT☐ **MONOFASE 230V / SINGLEPHASE 230V AC**☐ **TRIFASE 230/400V / THREEPHASE 230/400V AC**☐ **50 Hz**☐ **60 Hz****ALTRO / OTHER**